

MAXX-Pro

Housing-Specific Hybrids - 6.5" OD
Outside-In Polypropylene Microfiber with 226 O-rings

- Amines
- Hydrocarbon
- Chemical Plants
- Pipeline Fuels
- Process Water
- Waste Water
- Utility Water
- Cooling Water

The Strainrite Companies is proud to add the MAXX-Pro to our family of large pleat geometry products. The MAXX-Pro filters are high efficiency, outside to inside flow direction liquid filtration cartridges designed for applications with high contaminant removal requirements. These filters are a direct replacement for the 3M 740™ series and others.

MAXX-Pro cartridges are for use in filter housings that accept 6.5" (165 mm) outside diameter filter cartridges with 226 O-ring connections. The large diameter, ultra high surface area pleated cartridges are designed to provide the optimum combination of particle removal efficiency and contaminant holding capability with comparatively low flow resistance. Microfiber forms the basis of the filtration media utilized in MAXX-Pro filter cartridges.

Strainrite's manufacturing processes allow for tightly controlled specifications resulting in a filter media with consistent and predictable particle retention characteristics. MAXX-Pro cartridges are offered in micron grades ranging from 1 µm to 70 µm, and are typically used to remove solid contaminants.

740™ is a trademark of the 3M Corporation.

Features & Benefits



MAXX-Pro

- Large diameter pleat configuration for high flow rates
- High dirt holding capability due to extensive surface area
- 99% rated filter media for consistent and repeatable performance
- Injection molded cage for superior strength and element integrity
- Thermally bonded construction
- Variable pleat geometry ensures maximized usable surface area

MAXX-Pro O-ring

- Extremely low risk of by pass for high quality fluids.
- No loose parts to assemble for easy installation.
- No springs or caps to lose reduces the risk of by pass.
- Broad chemical compatibility for many applications.
- Convenient handle for easy removal.

Performance Characteristics



Specifications

Micron Rating

1, 2, 5, 10, 15, 25, 40, 70

Maximum Operating Temperature

180°F (82°C) Continuous Duty

Maximum Flow Rates

40" - 60-80 gpm

Recommended Change-out

35 psid

Materials of Construction

Filter Media

Polypropylene Microfiber

End Caps

Polypropylene

Support Material

Polypropylene
Polyester

Molded Cage

Polypropylene

O-rings

Buna N
Fluorocarbon
EPDM
Silicone
FEP Encapsulated Silicone

Sealing

Thermal Bond

Dimensions

MAXX Pro

**Nominal Top
Outside Diameter**
6.5" (16.5 cm)

Lengths
40" (101.6 cm)

Ordering Information

